





PISA 2816



Magnetically Shielded

Engineer's Kit: EK-PISA2816-X



Part No	Inductance	f _L	Tol	DCR max	Rated DC Current
	L (µH)				
PISA2816-2R2M-04	2.2	1	20	45	2.20
PISA2816-3R3M-04	3.3	1	20	45	2.00
PISA2816-4R7M-04	4.7	1	20	45	2.00
PISA2816-100M-04	10	1	20	52	1.84
PISA2816-120M-04	12	1	20	58	1.71
PISA2816-150M-04	15	1	20	81	1.47
PISA2816-180M-04	18	1	20	91	1.31
PISA2816-220M-04	22	1	20	110	1.23
PISA2816-270M-04	27	1	20	150	1.12
PISA2816-330M-04	33	1	20	170	0.96
PISA2816-390M-04	39	1	20	230	0.91
PISA2816-470M-04	47	1	20	260	0.88
PISA2816-560M-04	56	1	20	350	0.75
PISA2816-680M-04	68	1	20	380	0.69
PISA2816-820M-04	82	1	20	430	0.61
PISA2816-101M-04	100	1	20	610	0.60
PISA2816-121M-04	120	1	20	660	0.52
PISA2816-151M-04	150	1	20	880	0.46
PISA2816-181M-04	180	1	20	980	0.42
PISA2816-221M-04	220	1	20	1170	0.36
PISA2816-271M-04	270	1	20	1640	0.34
PISA2816-331M-04	330	1	20	1860	0.32
PISA2816-391M-04	390	1	20	2850	0.29
PISA2816-471M-04	470	1	20	3010	0.26
PISA2816-561M-04	560	1	20	3620	0.23
PISA2816-681M-04	680	1	20	4630	0.22
PISA2816-821M-04	820	1	20	5200	0.20
PISA2816-102M-04	1000	1	20	6000	0.18

Core Material: Ferrite
Base Material: Plastic

Revision date: 29 Nov 2023

SPQ: Taped / Reel 1000 [-04]

Remarks: - Additional gluing to PCB board is recommended.
- I - see description in Inductors Technical Data.